

Velourzusatz

Technical Information

- Characteristics:** **Rosner Velourzusatz** can be used as effect additive for all Rosner paint systems and helps to achieve a coarse to fine textured surface. A perfect result can only be achieved by carrying out the following instructions.
- Area of application:** Suitable as paint additive for effect coatings for furniture and interior fittings. For high-quality and resistant, coloured and transparent coatings of furniture in kitchens, offices, schools and homes as well as hotel and catering facilities. Also suitable for coloured and transparent coatings on glass substrates.
- Substrates:** Perfectly dry, clean substrates that have been treated accordingly to achieve the desired effect. The substrate must be solid.
- Mixing ratio:** Recommended quantity to add to the paint: 5% by weight (50 g/l)
ATTENTION: Mechanical stirring!
- Processing:** **Rosner Velourzusatz** is added by weight. It is important to ensure that the additive is added before adding the hardener, as the total amount of paint and additive must be cross-linked with hardener. The additive must be stirred into the basecoat thoroughly by machine. The quantity of the additive may also be less than 5%. For a higher amount, do not add more than 10%.
IMPORTANT:
An application by Airmix is possible only to a limited extent as this may cause mottling. If you use **Rosner Velourzusatz fein**, mottling can occur even when using a gravity spray gun. When working with Airmix, make sure that suitable filters are used, as too fine filters get clogged.
- Dilution:** **Rosner Velourzusatz** is ready for use. Depending on the process and requirements, the ready-to-use paint-hardener mixture can be diluted with **DD-Verdünnung Nr. 20**. Use **DD-Verdünnung Nr. 25** to retard the drying.
- Cleaning of tools:** **Waschlöser Nr. 52** and **PUG Pinsel- u. Gerätereiniger**.
- Storage:** **Rosner Velourzusatz** can be stored for at 3 years in tightly closed original containers. Paints that have been mixed with **Rosner Velourzusatz** tend to a higher sedimentation rate. In case of long storage, the paint must be stirred thoroughly prior to use.
- Special remarks:** **Rosner Velourzusatz** must be stored before every use. **Rosner Velourzusatz** is available with different grain sizes: **fine, standard** and **coarse**.

Please turn over!

Velourzusatz

Technical Information

Please consider:

The product and the recommendations in this technical data sheet correspond to today's state of the art. Our oral and written application recommendations, that are based on years of experience and provided to the best of knowledge, are non-committal and do not establish a contractual relationship and secondary obligation of the sales contract. They do not release the user from his obligation to verify on his own responsibility the existing substrate and the suitability of our products for the intended purpose. In case of doubt, suitability and spreading rate are to be tested by creating a sample. If our products are combined or intermixed with third-party products, we cannot guarantee a perfect surface finish.

Our general terms and conditions apply.

This technical data sheet replaces all previous versions.

Edited 11/19